



## CARLO Alu

Classic 230

The ideal tool for safe and effortless lifting, repositioning and transferring of heavyweight residents

# CARLO Alu, Classic 230

offers maximum safety and comfort ...



## The ideal solution for residents up to 230 kg ...



The CARLO Alu, Classic 230, patient hoist has been developed specifically for lifting, repositioning and transferring residents who are limited in their mobility and have a maximum patient weight of up to 230 kg.

Due to the special construction made of aluminium and steel components, the hoist is very easy to manoeuvre but nonetheless provides the stability required for the care of heavyweight residents. The extra wide sling hanger bar made of stainless steel is suitable for all loop slings; it is provided with a safety locking mechanism to attach the slings and is characterised by a patent-pending adjustment option to reduce rotation.

Along with a huge lifting range, the CARLO Alu, Classic 230, also convinces through its large and free range of rotation. This allows for the resident to be easily brought into the desired nursing position, without him hitting his legs or knees.



## Benefits for your nursing staff and your residents ...

- ❑ Light but nonetheless stable construction made of aluminium/steel
- ❑ Extra light and easy to manoeuvre
- ❑ High-quality lockable double castors
- ❑ Electrical height adjustment and electrically spreadable carrier frame
- ❑ No unsettling pendular or rotational movements during lifting and transferring, with patent-pending adjustment option to reduce rotation
- ❑ Hand control with display of battery charge status
- ❑ Working in an ergonomic and health-orientated manner, as no manual lifting is required
- ❑ Large and free rotating area for the resident
- ❑ 4-point sling hanger bar made of stainless steel, suitable for all loop slings
- ❑ Battery and charger compatible with all BEKA Hospitec hoists
- ❑ Also available with patient scale



## Technical data of the CARLO Alu, Classic 230

Carrier frame (length/height)	1.400 mm / 125 mm
Inner width (closed)	540 mm
Outer width (closed)	700 mm
Total width of the lift (carrier frame closed)	700 mm
Lifting range	1.400 mm
Max. patient weight	230 kg
SWL	230 kg
Drive	24V LINAK drive

## Accessories/Options

Digital patient scale
Transfer slings with loops (available in different sizes, standard sizes S-XXL)
Bathing slings with loops (available in different sizes, standard sizes S-XXL)
Toilet slings with loops (available in different sizes, standard sizes M-XL)
Spare battery 24V
External wall charging unit

