

Datasheet Wall Charger (5264 & 5265)

Functions	Value/unit/description
Installation	Wall or power outlet
Operation (input)	Charging of the batteries of a PLS Ceiling Hoist when Hand Control is placed on the Wall Charger.
Operation notification	Green LED on the Hand Control
Power Supply Unit (PSU) (Wall Charger 5264)	Mascot 2240B (<i>internal mascot</i>)
Power Supply Unit (PSU) (Wall Charger 5265)	Mascot 2240 (<i>external mascot</i>)
Compliance Mascot 2240(B)	Medically certified *see https://mascot.no/catalog/2240-la/c-24/p-140 for detailed compliance information
Input Voltage	90-264 V/AC
Maximal Output Voltage	+29,4 V/DC
Maximal Output Current	0,5 A
Stand-by voltage	+27,4 V/DC
Frequency	50-60 Hz
Protection	Reversed polarity and short circuit
Temperature range (operating)	-10 °C - +40 °C
Temperature range (storage)	-25 °C - +85 °C
Switch-off time when not in use	NA
Weight (Wall Charger 5264)	0,39 Kg 0,86 lb
Weight (Wall Charger 5265, exclusive Mascot)	0,32 Kg 0,70 lb
Sound level (operation)	NA
IP-rating (when installed)	IP-52
Material Housing	ABS with the Safety of Flammability UL 94 V-0
Colour	RAL 7035
Compliance POGO pins	RoHS & HF
Durability POGO pins (minimum)	+10000 cycles
Material POGO pins	Brass
Plating POGO pins	gold 10 micro-inch over 50~120 micro-inch nickel
IP-rating POGO pins (waterproof)	IP-x5
Dimensions (mm)	See drawing next page

