



TILSTSMART STANDARD ELS



ELEVAND TILSMART STANDARD ELS


The Elevand TiltSmart Standard ELS is designed with reinforced steel construction to support heavier loads, accommodating patients up to 230kg. Ideal for hospital wards, rehabilitation centres, nursing homes, and home care, this lift ensures maximum safety and comfort for daily patient care. It features a 4-point sling spreader bar, which can be lowered to the floor using a hand control, allowing a single carer to safely lift a person who has fallen. The electrically adjustable base leg spreading enhances manoeuvrability and ease of use. This lift combines durability, ease of operation, and efficiency, making it an essential tool for various care environments.

FEATURES

Reinforced Construction
Capable of lifting patients up to 230kgs (bariatric)

Battery Operation
Supports 20 complete lifting and lowering cycles on one charge (with max. load of 230kgs)

Compatible Spreader Bars
Fixed 4-point Spreader Bar
Manual 4-point Spreader Bar


Maximum Safe Working Load
230kgs

Electric Base
leg spreading

TECHNICAL SPECIFICATIONS

Base leg spreading	Electrical	Lifting Speed (raising/lowering)	36s/34s
Max. safe working load (SWL) (Kg)	230	Power req./Charger	100-200V/50-60Hz
Length/ Width (cm)	130/67	Remote control functions	Up/down
Height (cm)	135		Elec. leg spread
Lifting range(cm)	68-196		Outside/inside
Min.turning diameter (cm)	144		Battery charge status
Min.base legs width (int./ext.)(cm)	52/67		Service indicator
Max.base legs width (int./ext.)(cm)	103/118		Overload indicator
Base legs height (cm)	11.5	Packed Dimensions (LxWxH)(cm)	150x80x155
Castors diameter (cm)	10		
Weight (kg)	61		
Battery Capacity	2.9		

AVAILABLE DOWNLOADS



 [Instruction for Use](#)  [Quick Start Guide](#)  [Technical Specifications](#)