



CARLO Trend EP 185

The ideal tool for safe and effortless lifting, repositioning and transferring of your residents who are limited in mobility

CARLO Trend EP 185

offers maximum safety and comfort ...



- ✓ Electrical Positioning System (EPS)
- ✓ Anti-rotation mechanism (ARM)
- ✓ SWL: 185 kg



Benefits for your nursing staff and your residents ...

- ❑ Carrier frame and lifting column made out of aluminium and steel
- ❑ Extra light and easy to manoeuvre
- ❑ High-quality lockable double castors
- ❑ Electrical height adjustment and electrically spreadable carrier frame
- ❑ 4-point clip spreader bar can be lowered to the floor
- ❑ Electrical positioning system (EPS) in order to place the resident exactly without additional force
- ❑ No unsettling pendular or rotational movements during lifting and transferring
thank to patented anti-rotation mechanism (ARM)
- ❑ Can easily pass underneath both bath tubs and care beds
- ❑ Hand control with display of the battery charge status
- ❑ Working in an ergonomic and health-orientated manner,
as no manual lifting is required
- ❑ 4-point clip spreader bar
- ❑ Battery and charger are compatible with all
BEKA Hospitec hoists!
- ❑ Large choice of comfortable clip slings of different sizes
- ❑ Also available with patient scale



Technical data CARLO Trend EP 185

| | |
|---|-------------------|
| Carrier frame (length/height) | 1.290 mm / 125 mm |
| Inner width (closed/spread) | 540 mm / 1.040 mm |
| Outer width (closed/spread) | 700 mm / 1.180 mm |
| Total width of the lift (carrier frame closed) | 700 mm |
| Lifting range | 1.400 mm |
| Max. patient weight | 185 kg |
| SWL | 185 kg |
| Drive | 24V LINAK drive |

Accessories / Options

| |
|---|
| Patient scale |
| Transfer slings with clips (available in different sizes, standard size S-XXL) |
| Bathing slings with clips (available in different sizes, standard size S-XXL) |
| Toilet slings with clips (available in different sizes, standard size S-XL) |
| Soft slings with clips (available in different sizes, standard size S-XL) |
| Spare battery 24 V |
| External wall charging unit |

